

POWERVER

Security Plus II Series UPS

2 / 3 / 4 / 5.2 / 6 / 8 / 10 kVA

SECURITY PLUS II

The Security Plus II Series delivers a powerful combination of industry leading capacity, efficiency, and user-friendly features — all within a sleek, space-saving footprint — to ensure seamless performance and a positive return on your investment.

The Security Plus II Series features Powervar's proven low impedance isolation transformer technology and an unprecedented load inrush capacity so oversizing, and overspending, is never an issue. Customizable PDUs and front access allows quick and easy on-site connection and serviceability. The result is the most reliable power protection available and a lower total cost of ownership.



Advanced Power Protection for Mission Critical Applications

Industry Leading Technology

- Low impedance isolation transformer
- High load inrush capacity
- Impressive 1.0 output Power Factor
- Wide input voltage range
- Low input THDi
- Low-tolerance voltage regulation
- High output efficiency, up to 90%
- Internal Maintenance Bypass

Compact Footprint

- Conserve valuable floorspace
- Lighter shipping weight

User-Friendly Design

- Customizable back panel for direct plug-in installation
- Front access serviceability with hot swappable batteries
- Conformal coating circuit board protection
- Ultra-quiet operation

Smart System Management

- Integrated SNMP card slot
- Programmable LCD display screen
- Energy saving ECO mode
- Three-year warranty (two-year on batteries)





Sleek Space Saving Design – 32.5” H x 9.8” W x 28.3” D

Low Voltage	Load Power (kVA)	Input Voltage (VAC)	Output Voltage (VAC)	Input Plug	Output Receptacles	Frequency (Hz)	Ship Weight lb (kg)
ABCDEF2002-11	2.0	120	100-120	Option Available	Option Available	50/60	283 (128)
ABCDEF3002-11	3.0	120	100-120	Option Available	Option Available	50/60	353 (160)

High Voltage	Load Power (kVA)	Input Voltage (VAC)	Output Voltage (VAC)	Input Plug	Output Receptacles	Frequency (Hz)	Ship Weight lb (kg)
ABCDEF2002-22	2.0	208-240*	200-240*	Option Available	Option Available	50/60	283 (128)
ABCDEF3002-22	3.0	208-240*	200-240*	Option Available	Option Available	50/60	353 (160)
ABCDEF4002-22	4.0	208-240*	120-240*	Option Available	Option Available	50/60	353 (160)
ABCDEF5002-22	5.0	208-240*	120-240*	Option Available	Option Available	50/60	353 (160)
ABCDEF6002-22	6.0	208-240*	120-240*	Option Available	Option Available	50/60	353 (160)
ABCDEF8002-22	8.0	208-240*	120-240*	Option Available	Option Available	50/60	408 (185)
ABCDEF10.2-22	10.0	208-240*	120-240*	Option Available	Option Available	50/60	408 (185)

* 200, 208, 220, 230 & 240 volt solutions.
 * Contact factory for input and output options.

Case Dimensions (H x W x D) – in. (mm):
 A Case – 32.5 x 9.8 x 28.3 (825.5 x 248.9 x 718.4)



www.powervar.com
 1450 Lakeside Drive | Waukegan, IL 60085
 Tel. 800.369.7179 | 847.596.7000 | Fax 847.596.7100